

SPECIFICATION :

type		12.4M Three-axle Straight neck Stake Semi Trailer
Model		
parameter	dimension(mm)	length×width×height:12400×2500×3600
	dropside height(mm)	600
	column height(mm)	400+400
	king pin setting(mm)	1200
	fifth wheel height(mm)	The height will be adjusted according to the tractor specification
	axle space(mm)	7450+1310+1310
	tare weight (kg)	8,000
	payload (kg)	40,000
	GVWR (kg)	48,000
Fabric	main beam(mm)	500,submerged arc welding
	flange and web(mm)	14/10/16
	side rail	160mm high fabricalble "C" type channel.
	cross member	fabricalble "W" channel
	floor	3mm checker plate
	Rope device	10 rope device on each side of the platform
	paint	primer + top coat,polyurethane paint
OEM	landing gear	JOST C200T
	kingpin	2"JOST ,exchangeable
	brake system	30/30 type on each axle,WABCO brake valve
	ABS	No
	suspension	Mechanical suspension with 8 leaf spring
	axle	FUWA 13T, ISO10 Holes
	tire	Triangle Brand, type: 11R22.5 ,Linglong brand,equip 12 per chassis
	rim	8.25*22.5, ISO10, equip 12 per chassis
	tool box	1 set, steel box,1m
	spare tire carrier	2 units per chassis
color		Following customer's request.
paulin		1set
others		<ul style="list-style-type: none"> ● "LONG VEHICLE" sign on the rear end. ● LED lights, equip side turn light. ● Nameplate:English model ● Side Guard: Standard.

Note:

All the details not mentioned above should comply with Chinese regulations.
CIMC does NOT take any responsibility on the trailer's registration in the terminal country.

Reference Photo:

