

XCMG Tipper徐工自卸车

Model: XGA3312H2KC (371HP/8×4/25m³)Tipper自卸车

Dimensions(mm)/尺寸 (毫米)

Overall size (length×width×height) 外形尺寸 (长×宽×高)	10018×2495×3380
C a r g o b o d y s i z e (length×width×height) 货厢尺寸 (长×宽×高)	7200×2300×1500
Wheelbase轴距	2100+3400+1500
Wheel tread (Front/Rear) 轮距 (前/后)	2047 /1848
Min. ground clearance最小离地距离	280



Weight(kg)/重量 (公斤)

Kerb mass整备质量	13500
Gross vehicle weight总质量	41000
Rated loading capacity额定载质量	27500

Performance/性能参数

Max. travel speed最高车速	90km/h
Min. turning diameter最小转弯直径	25m
Max. gradeability爬坡度	25%
Approach angle 接近角	26°
Departure angle离去角	21°

Engine/发动机

WD615.47, water-cooling, turbocharging and intercooling, Euro II emission standard, direct injection diesel 水冷, 涡轮增压, 中冷, 欧II排放标准, 直喷式柴油机	
Rated output at 2200rpm额定功率	371HP(273kw)
Max. torque at 1200-1600 rpm最大扭矩	1460N.m

Driver's Cab/驾驶室

Tilttable cab, with air-condition & ventilation, adjustable driver's seat, single sleeper 可翻转驾驶室, 带空调和通风系统, 可调式司机座椅, 单卧铺
--

Transmission/变速箱

Front axle/前桥

9T curve

Rear axle/后桥

16T×2 Steyr technology, 13 layer blade block
双驱动桥, 全浮式半轴, 轮边减速

Ratio速比:5.92

Clutch/离合器

Diaphragm spring clutch, diameter 430
430膜片式弹簧离合器

Brakes/刹车

Service brake: dual circuit compressed air brake
行车制动: 双回路空气制动

Parking brake: spring energy operating on rear wheels
停车制动: 后轮弹簧气室制动

Auxiliary brake: engine exhaust brake
辅助刹车: 发动机排气制动

Wheels rim& Tyres/轮胎

Rims钢圈	8.50V-20
Tyres轮胎	13R22.5

Electric System/电力系统

Negative grounded负极搭铁

Operating voltage操作电压 24V

Type (型号) : 9JSD150A
9 forward/1 reverse 前进9档/后退1档

Alternator交流发电机 70A/28V
Batteries电瓶 6-QAW-180

Steering/转向装置

Hydraulic steering with power assistance液压助力转向

Fuel tank/油箱

Capacity容积 400 L

All specifications are subject to modifications without notice.
本公司保留随技术改进而修改参数的权利