

XCMG Timber Haulage Tractor 徐工木材运输牵引车

Model: NXG5250 (420HP/6×4) Timber Haulage Tractor 木材运输牵引车

Dimensions(mm)/尺寸(毫米)

Overall size (length×width×height) 外形尺寸(长×宽×高)	8420×2500×3670
Cargobody size (length×width×height) 货厢尺寸(长×宽×高)	/
Wheelbase 轴距	3800+1450
Wheel tread (Front/Rear) 轮距(前/后)	2006/1884
Min. ground clearance 最小离地距离	420

Weight(kg)/重量(公斤)

Kerb mass 整备质量	13920
Gross vehicle weight 总质量	24995
Rated loading capacity 额定载质量	10950

Performance/性能参数

Max. travel speed 最高车速	72km/h
Min. turning diameter 最小转弯直径	15m
Approach angle 接近角	29°
Departure angle 离去角	35°

Engine/发动机(潍柴)

WD12.420, water-cooling,turbocharging and intercooling, Euro II emission standard, direct injection diesel 水冷, 涡轮增压, 中冷, 欧II排放标准, 直喷式柴油机	
Rated output at 2,200rpm 额定功率	420HP(309kw)
Max. torque at 1300-1600 rpm 最大扭矩	1750N.m

Driver's Cab/驾驶室(新款宽体驾驶室)

Tiltable cab, with air-conditioner & ventilation, adjustable driver's seat 可翻转驾驶室, 带空调和通风系统, 可调式司机座椅

Transmission:变速箱(法士特)

Type(型号):J9SD220 9 forward/1 reverse 前进9档/后退1档

Steering/转向装置

Hydraulic steering with power assistance 液压助力转向



Front axle/前桥

7.5T

Rear axle/后桥(篷翔车桥)

16T

Ratio 速比:6.733

Clutch/离合器

Diaphragm spring clutch, diameter 430
430 膜片式弹簧离合器

Brakes/刹车

Service brake: dual circuit compressed air brake
行车制动: 双回路空气制动
Parking brake: spring energy operating on rear wheels
停车制动: 后轮弹簧气室制动
Auxiliary brake: engine exhaust brake
辅助刹车: 发动机排气制动

Wheels rim& Tyres/轮胎

Rims 钢圈	8.50V-24
Tyres 轮胎	12.00-24 18PR

Electric System/电力系统

Negative grounded 负极搭铁	
Operating voltage 操作电压	24V
Alternator 交流发电机	70A/28V
Batteries 电瓶	6-QAW-165

Fuel tank/油箱

Capacity 容积	400 L
-------------	-------

All specifications are subject to modifications without notice.
本公司保留随技术改进而修改参数的权利