

XCMG Tractor 徐工牵引车

Model: XGA4250D2KC (371HP/6×4) Tractor 牵引车

Dimensions(mm)/尺寸(毫米)

Overall size (length×width×height) 外形尺寸(长×宽×高)	7042*2500*3195
Wheelbase 轴距	3400+1400
Wheel tread (Front/Rear) 轮距(前/后)	2057/1804
Min. ground clearance (Rear Axle) 最小离地距离(后桥下)	308mm

Weight(kg)/重量(公斤)

Kerb mass 整备质量	9660
Gross vehicle weight 总质量	49000
Rated loading capacity 额定载质量	39340

Performance/性能参数

Max. travel speed 最高车速	90km/h
Min. turning diameter 最小转弯直径	14m
Approach angle 接近角	18°
Departure angle 离去角	52°

Engine/发动机(杭发)

WD615.47, water-cooling,turbocharging and intercooling, Euro II emission standard, direct injection diesel 水冷, 涡轮增压, 中冷, 欧II排放标准, 直喷式柴油机	
Rated output at 2,200rpm 额定功率	371HP(273kw)
Max. torque at 1300-1600 rpm 最大扭矩	1460N.m

Driver's Cab/驾驶室(新款宽体驾驶室)

Tilttable cab, with air-conditioner & ventilation, adjustable driver's seat, with 1 sleeper.
可翻转驾驶室, 带空调和通风系统, 可调式司机座椅, 带卧铺

Transmission:变速箱(法士特)

Type(型号): 9JSD150A
9 forward/1 reverse 前进9档/后退1档

Steering/转向装置

Hydraulic steering with power assistance 液压助力转向



Front axle/前桥

7.5T, curve axle

Rear axle/后桥(神力车桥)

16T

Ratio 速比:4.42

Steyr tech, with 13 layer blade block

Clutch/离合器

Diaphragm spring clutch, diameter 430
430 膜片式弹簧离合器

Brakes/刹车

Service brake: dual circuit compressed air brake
行车制动: 双回路空气制动
Parking brake: spring energy operating on rear wheels
停车制动: 后轮弹簧气室制动
Auxiliary brake: engine exhaust brake
辅助刹车: 发动机排气制动

Wheels rim& Tyres/轮胎

Rims 钢圈	8.50V-24
Tyres 轮胎	13.00R22.5

Electric System/电力系统

Negative grounded 负极搭铁	
Operating voltage 操作电压	24V
Alternator 交流发电机	70A/28V
Batteries 电瓶	6-QAW-165

Fuel tank/油箱

Capacity 容积	400 L
-------------	-------

Version agreed 12.03.18

All specifications are subject to modifications without notice.
本公司保留随技术改进而修改参数的权利