

XCMG Tipper 徐工自卸车

Model: XGA3252H2KC (336HP/6×4/20m³) Tipper 自卸车

Dimensions(mm)/尺寸(毫米)

Overall size (length×width×height) 外形尺寸(长×宽×高)	8670×2495×3380
Cargobody size (length×width×height) 货厢尺寸(长×宽×高)	5800×2300×1500
Wheelbase 轴距	3850+1350
Wheel tread (Front/Rear) 轮距(前/后)	2047/1848
Min. ground clearance 最小离地距离	290

Weight(kg)/重量(公斤)

Kerb mass 整备质量	12400
Gross vehicle weight 总质量	32500

Rated loading capacity 额定载质量	20100
------------------------------	-------

Performance/性能参数

Max. travel speed 最高车速	80km/h
Min. turning diameter 最小转弯直径	23m
Approach angle 接近角	26°
Departure angle 离去角	31°

Engine/发动机

WD615.69 water-cooling,turbocharging and intercooling, Euro II emission standard, direct injection diesel 水冷, 涡轮增压, 中冷, 欧II排放标准, 直喷式柴油机	
Rated output at 2,200rpm 额定功率	336HP(247kw)
Max. torque at 1200-1600 rpm 最大扭矩	1350N.m

Driver's Cab/驾驶室(新款宽体驾驶室)

Tiltable cab, with air-conditioner & ventilation, adjustable driver's seat, single sleeper
可翻转驾驶室, 带空调和通风系统, 可调式司机座椅, 单卧铺

Transmission:变速箱(法士特)

Type(型号): 9JSD150A
9 forward/1 reverse 前进9档/后退1档

Steering/转向装置(湖北三环/江苏罡阳)

Hydraulic steering with power assistance 液压助力转向



Front axle/前桥

9T, curve

Rear axle/后桥

16T Steyr technology, 13 layer blade block
双驱动桥, 全浮式半轴, 轮边减速
Ratio 速比: 5.92

Clutch/离合器

Diaphragm spring clutch, diameter 430
430 膜片式弹簧离合器

Brakes/刹车

Service brake: dual circuit compressed air brake
行车制动: 双回路空气制动
Parking brake: spring energy operating on rear wheels
停车制动: 后轮弹簧气室制动
Auxiliary brake: engine exhaust brake
辅助刹车: 发动机排气制动

Wheels rim& Tyres/轮胎

Rims 钢圈	8.50V-20
Tyres 轮胎	13R22.5

Electric System/电力系统

Negative grounded 负极搭铁	
Operating voltage 操作电压	24V
Alternator 交流发电机	70A/28V
Batteries 电瓶	6-QAW-165

Fuel tank/油箱

Capacity 容积	400 L
-------------	-------

All specifications are subject to modifications without notice.
本公司保留随技术改进而修改参数的权利

